

KIL Trim Key in Lever Trim



Specifications

- ANSI:** ANSI A156.3, Grade 1
- ADA:** Meets ADA requirements ANSI A117.1
- Construction:** Steel, Zinc Dichromated Chassis with Secure Thru Bolted design
- Application:** Standard Duty lever trim option for 1000R & 2000R
(Not recommended for SVR devices, Heavy Duty LE trim recommended)
- Door Prep:** Installs in 2 1/8" 161 door prep
- Actuator:** Cross shaped stainless steel
- Lever:** 5" Solid Zinc Diecast lever - 2 7/8" total projection
- Lever Designs:** Flat (standard, shown above) Curved, Half Curved, S-A & S-B
- Rose:** 3 3/8" wrought brass roses
- Handing:** Non-handed Completely Reversible
- Door Thickness:** 1 3/4" standard - available for 2" thick doors, specify when ordering
- Functions:** Passage, Storeroom & Entry
- Cylinder Options:** 6 Pin Brass, C Kwy, with 2 Keys std., Prepared for Small format IC core (less core)
- Optional Keyway:** 11 Popular competitor keyways available with replacement cylinders
- Finishes:** US3, US4, US10B, US26, US26D
- Warranty:** Limited lifetime warranty



KIL - Storeroom IC



KIL - Entry IC