



Residential



Hospitality



Commercial

STEALTH ACCESS DOORS...

It's all about what you can't see.

Stealth Access Panels are glass fiber reinforced gypsum (GFRG) panels designed to blend seamlessly into drywall ceilings and walls. The ceiling access panels consist of a surround frame with pre-spotted fastener holes and a drop-in door. Also available in round, when circular light fixtures, speakers or smoke detectors are being used to maintain the aesthetic theme in the design. Stealth hinged panels also consist of a surround frame with pre-spotted fastener holes with a concealed hinge and lockable door for both wall and ceiling applications. Available in multiple, standard, commercial and residential (drop-in style only) sizes, Stealth panels are perfect for jobs where access is required at regular intervals. Lightweight and easily textured, the panels can be used in both new and retrofit construction across unlimited applications. Their design helps contractors work smarter, faster and better. The residential models incorporate an energy saving gasket seal that keeps attic temperatures from infiltrating living space. Original Stealth Brand Access Panels provide an aesthetically pleasing, "out of the closet" solution for a more attractive interior. STEALTH...It's the better way to do access panels! Original Stealth Brand Access Doors Do not Accept Imitations.

PRODUCT FEATURES

- ▶ Tapered edge for tape joint
- Easily textured
- Lightweight
- ▶ Smooth round edge
- ▶ Single trade installation
- ▶ Blends into surrounding drywall
- No shrinkage
- No cracking
- ▶ Perfect for retrofit applications
- ▶ Reduce labor costs





Original Stealth Brand Access Doors

Do Not Accept Imitations

Radius

HOW TO INSTALL STEALTH ACCESS PANELS



1. Frame the opening.



2. Mount Stealth surround with drywall screws.



3. Install drywall and place access panel in opening.



4. Tape and apply drywall compound.




5. Apply desired finish.



350 Thorens Ave Garden City Park, NY 11040 Toll-Free 888-634-3667 www.metropolitandoor.com

STEALTH PANELS TECHNICAL DATA

Shell Thickness	1/8" to 3/16"
Fastener Test Pull Out (wood stud)	525 lb avg.
Fastener Test Pull Out (metal stud)	215 lb avg.
Fastener Push Through Test	350 lb avg.
Fuel Contribution (ASTM E84-80)	0
Flame Spread (ASTM E84-80)	0
Smoke Index (ASTM E84-80)	5
Combustion (ASTM E84-80)	Non-combustible
Class A Non-Rated	_
CSI Code	CSI #08310



Ordering Information

Part Code	Access Opening	Overall Frame Dimension
COMMERCIAL AC	CCESS PANELS	
TR-AP009	9" x 9"	15" x 15"
TR-AP012	12" x 12"	18" x 18"
TR-AP016	16" x 16"	22" x 22"
TR-AP018	18" x 18"	24" x 24"
TR-AP024	24" x 24"	30" x 30"
RESIDENTIAL AC	CESS PANELS (with	gasket)
TR-APGR2230	22" x 30"	28" x 36"
TR-APGR3030	30" x 30"	36" x 36"
SPECIALTY ROUN	ID PANELS	
TR-RAP012	12" diameter	18" x 18"
TR-RAP016	16" diameter	22" x 22"
TR-RAP018	18" diameter	24" x 24"
TR-RAP024	24" diameter	30" x 30"
HINGED ACCESS	PANELS	
TR-HAP009	9" x 9"	15" x 15"
TR-HAP012	12" x 12"	18" x 18"
TR-HAP016	16" x 16"	22" x 22"
TR-HAP018	18" x 18"	24" x 24"
TR-HAP024	24" x 24"	30" x 30"

^{*} Custom sizes available. Call for more details.

Distributed by:





STEALTH STOCK

Stealth access are stock in six strategic warehouses across the USA. Most warehouse stock orders ship within 1-business day after ordering.

Stealth stock is comprised of Commercial drop-in panels and residential (with gasket) panels.

Call for availability on Stealth round panels, Stealth hinged panels and large quantity orders.

Now available in Round & Hinged.



