SM SERIES Light Commercial Cylindrical Lock Grade 3



SM SERIES GRADE 3 CYLINDRICAL LOCK



FEATURES

- Anti-Lockout Kick-Off Feature (Privacy), not Available on Tubular Locks
- 4 Mechanical Functions Privacy, Passage, Entry, Single Dummy
- More Durable Than a Tubular Lock
- Retrofits All Major Competitor
 Door Preps
- Adjustable Backset, 2-3/8" 2-3/4"
- Doors 1-3/8", 1-3/4" Thick • Wood or Metal
- 2-3/4" Diameter Rose Fits Narrow Stile Doors

TYPICAL APPLICATIONS

- Assisted Living
- Hospitality
- Multi-Family

PDQ FUNCTIONS

INDICATES RIGID LEVER

SPECIFICATIONS

FOR DOORS:	• 1-3/8" to 1-3/4" thick	
BACKSET:	• 2-3/4" - 2-3/8" Adjustable	
FRONT:	 2-1/4" x 1" 1/4" Radius (Default) 2-1/4" x 1" Square (Optional) Stainless Steel or Wrought Brass 	
STRIKE:	 Full Lip 1/4" Radius ASA and T-Strike available as options 	
ROSE:	• 2-3/4" DIA Wrought	
LATCHBOLT:	• 1/2" Throw	
HAND:	• Non-handed	
TRIM:	 Diecast lever Stainless Steel or Wrought Brass Roses Philadelphia and Miami Levers 	
KEYS:	• Two (2) per Lock	
KEYWAYS:	• SCC Default (Schlage C Compatible).	
FINISHES:	• 619 (US15) Satin Nickel	
COMPLIANCES:	Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings	
WARRANTY:	• One (1) year Limited Warranty	

FUNCTION	FUNCTION NUMBER	INSIDE OUTSIDE	DESCRIPTION	ANSI NUMBER
Passage	SM126		Latchbolt operated by both levers	F75
Privacy	SM176		 Latchbolt operated by outside lever Push button on inside locks lever Inside lever or closing door releases button Emergency opening from outside 	F76
Entry	SM182		 Latchbolt operated by lever from either side or key in outside lever Outside lever locked by push button on inside Outside lever unlocked by key from outside 	F82
Single Dummy	SM211		Single pull lever one sideSurface mount	_



HOW TO ORDER

SERIES	FUNCTION	LEVER	FINISH	BACKSET	STRIKE
SM	182	PHL	619	ADJR	_
				ADJR — Radius Corner (default) ADJ — Square Corner	FLR — Radius Full Lip (default) FLS — Full Lip T — "T" Strike ASA — ASA 4-7/8"

LEVER DESIGNS





TRIM



Round Rose -2-3/4" Diameter

FINISH




619 (US15) Satin Nickel, No Coating

BACKSET

CODE	DESCRIPTION	PDQ NO.
	SPRINGLATCH — 2-3/4" - 2-3/8" ADJUSTABLE	
ADJRKO	2-1/4" x 1" x 1/4"Radius Privacy	104407KR
	DEADLATCH — 2-3/4" - 2-3/8" ADJUSTABLE	
ADJR	2-1/4" x 1" x 1/4"Radius	104406
FILL	1-1/8" Latch Front Filler Plate (Minimum of 100 pieces)	1099-100

Springlatch



Deadlatch

STRIKES

CODE	DESCRIPTION	
FLR	Full Lip Strike Radius (default) (SM series only) 1-5/8" x 2-1/4" x 1/4" Radius V919010 (des- ignate finish)	
FLS	Full Lip Strike (SM series only) 1-5/8" x 2-1/4" V919004 (designate finish)	
т	T Strike (SM series only) 1-1/8" x 2-3/4" V919001 (designate finish)	
ASA	ASA Strike 1-1/4" x 4-7/8"	





SECURING CONFIDENCE OPENING POSSIBILITIES

Phone: 800.441.9692 Tech Support: 833.2.PDQTEC (833.273.7832) FAX: 717.656.6892 | Email: help@pdqlocks.com

Headquarters: PO BOX 507 | 2754 Creek Hill Road, Leola, PA 17540

Regional Distribution Centers: Leola, PA | Kansas City, MO Salt Lake City, UT | Auburn, WA

Design Office: Milan, Italy

pdqlocks.com