

# PCA® Perlator ® Faucet aerator - 1.5 gpm max

Tel: (800) 875-2955 Fax: (484) 944-1590 www.conservationwarehouse.com Certified WBE Company

Pressure compensating Tom Thumb® Size

#### **Features and Benefits**

- The smallest aerator available from NEOPERL®.
- ⇒ Pressure compensating for constant flow from 20 to 80 psi.
- ⇒ Anti-liming Honeycomb® replaces conventional wire mesh screens prone to lime build up.
- Anti-clogging dome screen filters sediment and particles.
- Color-coded to identify flow rate.
- Patented construction provides a splash-free stream, well aerated and soft to the touch
- a Available housing finishes: chrome.
- ⇒ Compatible with NEOPERL® Tom Thumb ® male and female housings.
- Rubber washer.

### Certification

#### ANSI/NSF 61

WaterSense listed



Designation & Thread Sizes		
Designation	Thread Size	
Insert only		
Tom Thumb male	M18 x 1	
Tom Thumb female	M16 x 1	

<sup>\*</sup>Other combinations also available

## Housings









Tom Thumb Female

Insert Color Code		
Dome: Clear / Green	Ring: White	Basket: Gray



Dimensions		
No	mm	In
Α	12.95	.510
В	15.00	.591
С	≈ 9	≈ 3/8





Technical Data	
Material:	
Body	Acetal
O-ring	EPDM
Washer	NBR
Working temperature:	150°F
Working pressure:	125 psi