

**Uni-Sport II Basketball System**

1. **WALL STRUT** – Wall strut shall be manufactured from .25 thick steel powder coated black. Strut shall be manufactured with a series of four elongated slots above and below the main extension arm for easy and secure mounting to wall.
2. **EXTENSION ARMS** - Main 45 degree extension arm tube shall be 2”x3” rectangular 11 gauge wall steel tubing and provide for a 24” extension from front of pole to face of backboard. Extension arm shall be constructed to allow rim bolts to pass through backboard and directly into extension arm for strength and player safety. Extension arm shall be secured to vertical post by means of two 4” zinc plated U-bolts. Additionally, two 1” round backboard braces shall support upper corners of the backboard.
3. **BACKBOARD** - Constructed of 3/8” thick acrylic with bright white screening. The framework shall be constructed from clear anodized aluminum “L” type extrusions. Overall backboard size shall be approximately 48” wide and 36” high.
4. **RIM** - Flexible type so as to absorb the stress of player contact. The rim shall be of institutional quality with an official 5/8” diameter ring. Ring opening diameter shall be the standard 18” I.D. Rim shall have an orange powder coated finish. Heavy-duty nylon net shall be provided.
5. **WARRANTY** - Strut, backboard, and standard rim shall carry Lifetime Limited Warranty. Entire system weight shall be approximately 170#.