



## First Team Sports, Inc. | Renegade Supreme

- 1. VERTICAL POLE** - Vertical post shall be constructed of 4 ½" O.D. RS40 zinc flow coated steel tubing with a 7 ga. wall thickness. Design shall allow for a 48" bury into the ground and a 48" setback from post to backboard. Two 1" round galvanized tubular braces shall support the top corners of the backboard and connect directly to the pole. The height of the rim shall be adjustable by clamping the 4 ½" diameter extension arm at the desired height on the vertical post. The pole shall be designed so that the rim mounts directly through the backboard into the horizontal extension to eliminate backboard stress during play. Pole systems where rim mounts to backboard only are not considered equal.
- 2. BACKBOARD** - Backboard shall be 42"x 72" rectangular 1/2" thick clear acrylic framed in a competition grade anodized aluminum framework. Backboard shall have bright white 2" boarder and official size shooter's square screen-printed on backside to eliminate wear.
- 3. RIM** - Standard rim shall be of a flexible type so as to absorb the stress of player contact. Spring action shall be provided by a heavy duty compression wire spring. A steel coverplate must enclose entire internal mechanism. All structural components shall be built of no less than 3/16" steel. Rim shall be of institutional quality with an official 5/8" diameter high strength steel ring supported by a 3/16" brace supporting 60% of the ring. Rim shall be punched to mount either a 3"x 4" or 5"x 5" hole pattern. Orange powdercoated finish.
- 4. WARRANTY** - Pole, backboard, and standard rim shall carry a 20-Year Limited Warranty. Entire system weight shall be approximately 295#.