



750 Eastcoast St South • Lake Worth, FL 33460  
561-588-6630 • Fax: 561-585-4141  
[www.uprproducts.com](http://www.uprproducts.com) • [talktoupr@uprproducts.com](mailto:talktoupr@uprproducts.com)

## UPR Oil Catch Can Installation

### 5028-164 /164-1 11-up 5.7, 6.4 with Shaker

1. Remove the Shaker Hood Cover for better access to the PCV hose and connectors.
2. Remove the factory PCV hose from the rubber connectors that attaches it to the intake and throttle body. These can be tough and you might need to twist them or slide a small screwdriver in between the hard plastic line and the rubber connector to break them free.
3. - You will twist the rubber connector at the throttle body to face the front passenger side fender so it can line up with the catch can as a straight shot. Now you can install the supplied UPR Nickel Hose Bars into the rubber connectors.
4. - Mount the catch can bracket onto the factory stud on the upper passenger side of the water pump. Using the supplied nut, tighten the bracket so that the catch can's top is parallel with the ground, and the catch can clears all hoses, belts, Shaker etc.
5. - Install the short hose from the front of the catch can to the rubber connector at the throttle body and then the long hose from the rear of the catch can to the rubber connector at the rear of the intake manifold. The Plug and Play fittings at the catch can are installed by simply pushing them onto the catch can fittings until they click. To remove them, just push the button on the side of the fitting to release it , and slide it off. Do not pry the clips from the Plug and Play fittings as this will destroy the clip and cause leaks.

When emptying the catch can, unscrew the bottom cup of the can and properly dispose of the oil, fuel,water, mixture that has collected. NEVER RETURN THIS MIXTURE TO THE ENGINE. Screw the catch can cup back on just snug to the body of the catch can - **never over tighten it** as the interference fit with the face mounted O rings is designed to just be snugged for easy maintenance. Always be sure to grip the top of the catch can when loosening or tightening the bottom.

Always check and drain the catch can more often in winter / freezing weather. If the water/oil mixture in the catch can is allowed to freeze it will cause damage to the catch can and internal components. Any damage due to freezing is NOT WARRANTY.



750 Eastcoast St South • Lake Worth, FL 33460  
561-588-6630 • Fax: 561-585-4141  
[www.uprproducts.com](http://www.uprproducts.com) • [talktoupr@uprproducts.com](mailto:talktoupr@uprproducts.com)

---

Thank you for choosing UPRproducts.com the very  
BEST Hemi Catch Can Systems available.

*Product Liability Statement:* *The purchase of the product,  
manufactured by UPR Products Inc. completes an agreement  
between UPR Products Inc. and the customer. UPR Products Inc.  
assumes no liability for damages or injury incurred by the buyer of  
this product. The buyer has complete responsibility for the  
installation, use and upkeep of this product.*

***Be sure to shop our online store for the best deals: [www.uprproducts.com](http://www.uprproducts.com)***