



### S 25 N - 18 G - ST Dispersing element

Suitable for dispersing instrument T 25 digital  
 ST tools are recommended for use with tissue and other fibrous materials  
 Working range: 10 - 1500 ml  
 Stator diameter: 18 mm  
 Immersion depth: 40 - 1655 mm  
 Materials in contact with medium: PTFE, AISI 316L  
 Suitable for solvents  
 Max. temperature: 180 °C  
 Sterilization methods: all methods

Technical Data	
Volume range min. (H2O) [l]	0.01
Volume range max. (H2O) [l]	1.5
Stator diameter [mm]	18
Rotor diameter [mm]	13.4
Gap between rotor and stator [mm]	0.25
allowable Speed max. [rpm]	25000
Circumferential speed max. [m/s]	17.5
Immersion depth min. [mm]	40
Immersion depth max. [mm]	165
Shaft length [mm]	194
Material in contact with medium	PTFE, AISI 316L
pH min.	2
pH max.	13
Suitable for solvents	yes
Suitable for abrasive substances	yes
Working temperature max. [°C]	180
Sterilization methods	all methods
Ultimate fineness, suspensions min. [µm]	10
Ultimate fineness, suspensions max. [µm]	50
Ultimate fineness, emulsions min. [µm]	1
Ultimate fineness, emulsions max. [µm]	10
<b>Ident. No.</b>	<b>0004447300</b>