

## SkyBell® Video Doorbell

SkyBell is a high-definition video doorbell that lets homeowners enjoy new levels of security, control and convenience wherever they are in the world. End-users can remotely check doorbell activity on the Honeywell Total Connect® 2.0 Remote Services app, and see, hear and speak to visitors at their doors from their iPhone® or iPad®.

The IP54-rated device is built to withstand the harshest outdoor climates, with a temperature range of -40°F to 140°F (-40°C to 60°C). As sleek and attractive as it is functional, the SkyBell Video Doorbell is a stylish addition to any home.

Part of a dynamic, growing ecosystem, this solution provides security dealers with an excellent way to drive RMR, deliver a great user experience and enhance their connected home offering.



Works with Honeywell Total Connect 2.0 Remote Services



## FEATURES & BENEFITS

- **Two-Way Audio**  
Homeowners can enjoy a full, two-way conversation with visitors from their iPhone or iPad
- **Motion Sensor**  
SkyBell Video Doorbell alerts homeowners when visitors are in front of their door, whether or not the button is pressed
- **Full Color Night Vision**  
Homeowners can feel safe knowing they can view visitors at night in color HD
- **On-Demand Monitoring**  
SkyBell is "Always On" so homeowners can start a live video stream at any time for remote monitoring.
- **Silent Mode**  
Homeowners can turn off their indoor chime and receive notifications on their iOS devices—perfect for when someone is sleeping

\*Audio and high-definition video viewing accessible through the SkyBell HD app.

# SkyBell® Video Doorbell Technical Specifications



## SYSTEM REQUIREMENTS

**Power Input:** Wired power connection to in-home mechanical door chime 10-36VAC, 10VA or 12V DC with an amp rate of 0.5 to 1.0

**Wi-Fi® Router:** 802.11 b/g/n, 2.4GHz

**Initial Set-up:** Requires use of smartphone or tablet and a high-speed Internet connection

**Operating System (smartphone/tablet):** Apple® iOS 8.1 or later, Android™ 2.X or later (Available soon)

## TECHNICAL SPECIFICATIONS

**Camera:** 1080p/720p HD

**Video:** H264 x 30FPS HD

**Microphone:** MEMS digital omnidirectional PDM

**Speaker:** 110 dB SPL @ 1 em, peak output 2 Watt

**Motion Sensor:** PIR detection 180° @ 15 ft.

**Night Vision:** Full Color Night Vision 15 ft.

**Field of View:** 180°

**Data Transfer Speed:** SuperSpeed 2x (150 MHz)

**Bluetooth:** Low energy

**Materials/Finish:** Oil Rubbed Bronze/Silver

**Battery:** Built-in for power regulation

**Operating Temperature:** -40°F to 140°F (-40°C to 60°C)

**Weather Proofing:** IP54

## DIMENSIONS

**Diameter:** 2.8 inches (7.1 cm)

**Depth:** 0.9 inches (2.2 cm)

**Weight:** 1.9 oz (53.8 g)

## POWER REQUIREMENTS

SkyBell requires a wired AC power source connection to a doorbell transformer, supporting either a mechanical door chime or a digital door chime\*.

**Voltage:** 120/130v AC or 220/230/240v AC

**Transformer Range:** 8-36v AC, 8-15 VA

**Low Voltage Transformer (UK/Europe):** 8-36v AC, 1-AMP 8-15 VA

**\*Digital Door Chime:**

Requires a digital adapter, available through SkyBell

## ORDERING

Video Doorbell Silver	DBCAM
Video Doorbell Bronze	DBCAM-BR

Honeywell's DBCAM and DBCAM-BR are intended for use with Honeywell control panels and Honeywell Total Connect® Remote Services.

## For more information

[www.SkyBell.com](http://www.SkyBell.com)

## Honeywell Security and Fire

2 Corporate Center Dr. Suite 100

P.O. Box 9040

Melville, NY 11747

1.800.323.4576

[www.honeywell.com](http://www.honeywell.com)

All other trademarks are the property of their respective owners.

L/SKYBELLD/D | 08/16

© 2016 Honeywell International Inc.

**Honeywell**