



SAFETY DATA SHEET

Issue Date 14-Jun-2011

Revision Date 12-Dec-2012

Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name Peel Away Deck Restorer

Other Means of Identification

SDS # DCI-015

UN/ID No UN3266
Synonyms Deck Restore Wood Restorer

Recommended Use of the Chemical and Restrictions on Use

Recommended Use Deck restoration.

Details of the Supplier of the Safety Data Sheet

Supplier Address

Dumond Chemicals, Inc.
 83 General Warren Blvd
 Suite 190
 Malvern, PA 19355

Emergency Telephone Number

Company Phone Number 1-609-655-7700
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
 1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1

Signal Word

Danger

Hazard Statements

Harmful if inhaled
 Harmful in contact with skin
 Causes severe skin burns and eye damage



Appearance Blue liquid**Physical State** Liquid**Odor** Mild**Precautionary Statements - Prevention**

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Immediately call a POISON CENTER or doctor/physician

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Deck Restore Wood Restorer.

Chemical Name	CAS No	Weight-%
Sodium metasilicate	6834-92-0	1-5
Sodium hydroxide	1310-73-2	1-6
2-Butoxyethanol	111-76-2	1-5

4. FIRST AID MEASURES**First Aid Measures****Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician if you feel unwell.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Immediate medical attention is required.

Ingestion

If conscious, give 1 glass of water or milk to dilute. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if necessary.

Skin Contact

Wash area with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a physician immediately.

Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Mists and vapors cause irritation of the eyes, mucous membranes, and upper respiratory tract. May cause pain, conjunctivitis of the eyes or burns. Contact with skin can cause irritation, (minor itching, burning an/or redness), dermatitis, defatting, may be readily absorbed through the skin. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Treat symptomatically. Prolonged overexposure to 2-butoxyethanol may cause adverse effects of the blood, kidneys, and liver. Individuals with chronic respiratory or skin diseases may be at risk from exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool fire exposed containers and structures with water.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

At elevated temperatures, containers may rupture. Contact with metals may evolve flammable hydrogen gas. Contents are corrosive and all personal contact must be avoided.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Use personal protective equipment as required.

Environmental Precautions Do not allow into any sewer, on the ground or into any body of water. See Section 12 for additional ecological information.

Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Keep in suitable, closed containers for disposal. Flush area with flooding quantities of water. Spills and releases may have to be reported to Federal and/or local authorities. See section 15.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Protect container from physical damage. Since empty container retains residue, follow all label warnings even after container is empty. Do not get in eyes, on skin, or on clothing. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use personal protection recommended in Section 8. Use only in well-ventilated areas. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions	Store in a cool, well ventilated area away from acids and other incompatible substances. Keep container tightly closed. Store locked up.
Incompatible Materials	Strong oxidizing agents. Alkali. Acids. Organic halogen compounds. Ammonia. Organic amines. Reducing sugars. Nitromethane.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Sodium hydroxide 1310-73-2	Ceiling: 2 mg/m ³	TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³	IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³
Sodium metasilicate 6834-92-0	2 mg/m ³	2 mg/m ³	-

Appropriate Engineering Controls

Engineering Controls	Showers Eyewash stations Ventilation systems. Apply technical measures to comply with the occupational exposure limits. If the recommended exposure limit is exceeded increased mechanical ventilation such as local exhaust may be required.
-----------------------------	---

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection	Wear safety glasses with side shields (or goggles). Face Mask. Do not wear contact lenses.
Skin and Body Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear protective butyl rubber gloves.
Respiratory Protection	Good general ventilation (equivalent to outdoors) should be adequate under normal conditions. For spray application or areas where TLV is exceeded, a NIOSH approved dust mist or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection of respiratory protection depends on the contaminant type, form, and concentration. Select in accordance with OSHA 1910.134 and good industrial hygiene.

General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.
---------------------------------------	--

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	Liquid	Odor	Mild
Appearance	Blue liquid	Odor threshold	Not determined
Color	Blue		
Property	Values	Remarks • Method	
pH	12		
Melting point/freezing point	Not available		
Boiling point/boiling range	100 °C / 212 °F		
Flash point	None		

Evaporation rate	Similar to water
Flammability (solid, gas)	Not determined
Flammability limits in air	
Upper flammability limits	Not applicable
Lower flammability limit	Not applicable
Vapor pressure	Not determined
Vapor density	Not determined
Specific gravity	1.11
Water solubility	Completely soluble
Solubility in other solvents	Not determined
Partition coefficient	Not available
Autoignition temperature	Not established
Decomposition temperature	Not determined
Kinematic viscosity	Not determined
Dynamic viscosity	Not determined
Explosive properties	Not determined
Oxidizing Properties	Not determined

Other Information

VOC Content (%)	< 2%
VOC Content	0.18 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children. Flammable hydrogen gas may be produced on prolonged contact with metals such as aluminum, tin, lead, and zinc.

Incompatible Materials

Strong oxidizing agents. Alkali. Acids. Organic halogen compounds. Ammonia. Organic amines. Reducing sugars. Nitromethane.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO₂). sodium oxides. Ammonia. Polyacrylates. Acrylic acid.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information	The product has not been tested
Inhalation	Harmful if inhaled.
Eye Contact	Causes serious eye damage.
Skin Contact	Harmful in contact with skin. Causes severe skin burns.
Ingestion	Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg (Rabbit)	= 2.21 mg/L (Rat) 4 h = 450 ppm (Rat) 4 h
Sodium hydroxide 1310-73-2	-	= 1350 mg/kg (Rabbit)	-
Sodium metasilicate 6834-92-0	= 600 mg/kg (Rat)	-	-

Information on Physical, Chemical and Toxicological Effects

Symptoms

Mists and vapors cause irritation of the eyes, mucous membranes, and upper respiratory tract. Causes painful stinging or burning of eyes and lids, watering of eyes. Prolonged contact may even cause severe skin irritation or mild burn. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity

Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3		

Chronic toxicity

Individuals with chronic respiratory or skin diseases may be at risk from exposure.

Numerical Measures of Toxicity- Product

Not determined

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	8787 mg/kg
ATEmix (dermal)	166 mg/kg
ATEmix (inhalation-gas)	23310 mg/l
ATEmix (inhalation-dust/mist)	1.7 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Sodium hydroxide 1310-73-2		45.4: 96 h Oncorhynchus mykiss mg/L LC50 static		
Sodium metasilicate 6834-92-0		210: 96 h Brachydanio rerio mg/L LC50 semi-static 210: 96 h Brachydanio rerio mg/L LC50		216: 96 h Daphnia magna mg/L EC50

Persistence and Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined.

Chemical Name	Partition coefficient
2-Butoxyethanol 111-76-2	0.81

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods**Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	California Hazardous Waste Status
Sodium hydroxide 1310-73-2	Toxic Corrosive

14. TRANSPORT INFORMATION

Note

Based on package size, product may be eligible for limited quantity exception

DOT

UN/ID No UN3266
 Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, sodium metasilicate)
 Hazard Class 8
 Packing Group II

IATA

UN/ID No UN3266
 Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, sodium metasilicate)
 Hazard Class 8
 Packing Group II

IMDG

UN/ID No UN3266
 Proper Shipping Name Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide, sodium metasilicate)
 Hazard Class 8
 Packing Group II

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

DSL Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	1-5	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Sodium hydroxide 1310-73-2	1000 lb			X
Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)	
Sodium hydroxide 1310-73-2	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ	

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
2-Butoxyethanol 111-76-2	X	X	X
Sodium hydroxide 1310-73-2	X	X	X

U.S. EPA Label Information

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	3	0	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date	14-Jun-2011
Revision Date	12-Dec-2012
Revision Note	New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet