







SPECIFICATIONS - CAT5E/5E-SH

SIMPLY45-CAT5E		
   TAA Compliant	Performance:	Meets or Exceeds ANSI/TIA 568-D.2; ISO/IEC 11801 Class D; ANSI/TIA 1096-A; IEC 60603-7
	Cat5e UTP Wire Cond(s) OD:	24AWG UTP, Up to 0.039"-0.041" (1.00mm-1.05mm)
	Max Cable Outer Diameter:	0.2402" (6.10mm)
	Supports PoE/PoH:	Yes
	Cable Fire Resistance Ratings:	CMP, CMR, CM, CMX, LSZH up to B2ca EuroClass
	Flame Autoextinguish:	UL94 V0, IEC 60695-11-10
	Contact Material:	Phosphor Bronze - .012" thick
	Contact Plating:	Min 50 Micro-Inch Pure Gold - 24 Carat Hard Gold Plate in contact area over 100 Micro-Inch Min Nickel Plating. Exceeds ANSI/TIA-1096-A specifications (formerly FCC Part 68)
	Plug Material:	Polycarbonate
	Plug Tolerances and Dimensions:	Meets ANSI/TIA-1096-A specifications (formerly FCC Part 68)
	Conductor Type(s):	Solid and Stranded
	Operating Temperature:	-40° C to +70° C
	Insertion/Extraction Life:	2000 Minimum Cycles
	Contact Resistance:	20 Milli-Ohms max
Current/Voltage:	30 VAC/42 VDC at 1.5 Amps	
Compliance:	UL Listed, RoHS, FCC, NEC, TAA	

SIMPLY45-CAT5E-SH		
<p>For CAT5E Solid STP CAT5E/6/6A Stranded STP</p>    TAA Compliant	Performance:	Meets or Exceeds ANSI/TIA 568-D.2; ISO/IEC 11801 Class D; ANSI/TIA 1096-A; IEC 60603-7
	Cat5e STP Wire Cond(s) OD:	24AWG STP, Up to 0.039"-0.041" (1.00mm-1.05mm)
	Max Cable Outer Diameter:	0.2402" (6.10mm)
	Supports PoE/PoH:	Yes
	Cable Fire Resistance Ratings:	CMP, CMR, CM, CMX, LSZH up to B2ca EuroClass
	Flame Autoextinguish:	UL94 V0, IEC 60695-11-10
	Contact Material:	Phosphor Bronze - .012" thick
	Contact Plating:	Min 50 Micro-Inch Pure Gold - 24 Carat Hard Gold Plate in contact area over 100 Micro-Inch Min Nickel Plating. Exceeds ANSI/TIA-1096-A specifications (formerly FCC Part 68)
	Plug Material:	Polycarbonate
	Shielded Material:	Hard Brass
	Shielded Plating:	80 Micro-Inch minimum Nickel Plating
	Plug Tolerances and Dimensions:	Meets ANSI/TIA-1096-A specifications (formerly FCC Part 68)
	Conductor Type(s):	Solid and Stranded
	Operating Temperature:	-40° C to +70° C
Insertion/Extraction Life:	2000 Minimum Cycles	
Contact Resistance:	20 Milli-Ohms maximum	
Current/Voltage:	30 VAC/42 VDC at 1.5 Amps	
Compliance:	UL Listed, RoHS, FCC, NEC, TAA	

Learn more today by visiting our website: www.scp5e.com/simply45 or email us at sales@scp5e.com

SIMPLY45™ is a trademark of Simply45 LLC. © All rights reserved.