

Signal Specifications

- Video Signal Support - VGA
- Audio Signal Support - Stereo Audio
- Maximum Video Resolution - 1920x1080 or 1920x1200
- Maximum Cable Distance - 300ft
- Recommended Category Cable - Solid Cat5e or Cat6*

*Solid conductor Cat5 or Cat6 cabling is recommended for use with the digital products, HDMI and HDMI with RS232. Coiling of excess cable lengths should be avoided for best performance results. Shielded, solid conductor Cat5 or Cat6 cabling is recommended if a cable must be coiled or is run near other high-frequency signaling cables.

Power Adapter Specifications

- Input Voltage - 100-240V
- Output Voltage/Amperage - 18V, 1.0A
- Cable Length - 1.5m
- Plug Diameter - 4.75mm
- Center Pin Polarity - Positive

Physical Characteristics

- Video Ports - HD15 Female
- Audio Ports - 3.5mm Female
- Data Ports - RJ45 Female x 2

Additional Specifications

- Source device with a standard VGA video and stereo audio outputs
- One transmitter, box or wall plate
- Two standard UTP cables*
- (CAT5, Cat5e, CAT6) of identical length• One receiver, box or wall plate
- Display device with a standard VGA and stereo audio input

* Cat5e or CAT6 is recommended for this product. CAT6 cabling will support a higher picture quality than Cat5e. STP cabling is recommended for environments with high EMI or RFI.